

JC077020BLK


Line Of Light

Line of Light 1500mm 16/18/20/22W IP20 3000/4000/5700K Black



Features & Benefits

- Two-part construction allowing easy access to termination and internal components
- Available in 4ft and 5ft lengths
- Available in white, silver and black
- Colour selectable between 3000K, 4000K & 5700K
- Illuminated corners & upward illumination options
- Suspension kit available
- Linking kit (JC077156) available to assemble longer lengths, squares and rectangle configurations
- Sections and corners can be connected via a simple plug and play system
- For longer seamless runs add /EXT to any standard Line of Light product codes to order middle/end pieces that exclude end caps and flex



General Information

Mounting	Surface or Suspended
Suitable For Zones	Outside Zone 2
Product Group	Commercial Linear
Color Finish	Black
Product Shape	Rectangular
Product Range	Line Of Light
Overall Dimensions	1205 x 60 x 78
Length (mm)	1205
Width (mm)	60
Height (mm)	78
Light Source	LED
Light Source Features	3CCT Selectable
Additional Information	It is advised not to mix 1205mm and 1505mm fittings on the same connected layout- surface diffuser brightness may vary between the different lengths

Luminaire Accessories	JC077156 linking kit, JC077150 Corner(add BLK/SIL/WH), JC077153 2m suspension kit(add BLK/SIL/WH), JC077154 5m suspension kit(add BLK/SIL/WH)
Fixing centres	See instruction hseet
IP Rating	20
Origin of manufacturer	China
Warranty	5 Year Warranty(Terms & conditions apply)
Operation Type	On/off
Driver manufacturer	BOKE
LED manufacturer/type	Shaanxi/2835
Customs Tariff code**	9405119090

Electrical

Voltage Rating	220-240
Primary Running Current(Amp)	0.135
Inrush current(Amps)	4.025A peak ,153us duration(50 % Ipeak)
Operating Frequency Hz	50/60Hz
Secondary running current(mA)	400/450/500/550
Constant Current or Constant Voltage	CC
Luminaire Circuit Wattage	24/32/40
Class	I
Output Voltage Max/Range (VDC)	24-42
Total Harmonic Distortion (THD)%	8
EMC Compliant (EN55015)	Yes
Power Factor Correction	0.98
Input Electrical Connections	Live, Earth, Neutral
Dimmable	No

Thermals

Thermal Cut Out	yes
Operating Temperature Range °C	-20 to 60

Performance Data

LED Life (Hours)*	36000
Energy Rating	This product contains a light source of energy efficiency class E
Actual Lumen Output	1800/2050/2250/2450
Lumens Per Circuit Watt	113/114/113/111
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	3000/4000/5700
Beam Angle °	75
LOR (Light Output Ratio) %	100
Photometry Available	Yes

Construction

Primary Material

Aluminium

Outer Diffuser

Polycarbonate

Driver Housing

Polycarbonate

Packaging

Product Bar Code EAN-13 Number

5052544125553

Standards & Approvals

Manufactured in accordance to

BS EN 60598-2-1

CE Marked

Yes

UKCA Marked

Yes

Date code/Purchase order No.

Yes

WEEE symbol


Yes


Certificate Of Conformity

Available on request

Accredited Members

LIA, ISO9001-2015, ISO14001-2015





*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

**JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT.
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 106 [04/02/2025]