

JC71743PIR

Skypack QR

Skypack QR LED Batten 5ft Single 37W IP20 4000K 4440lm PIR

Features & Benefits

- Intelligent press release buttons for simple installation
- Ultra efficient up to 120 lumens per circuit Watt
- Suspended LED tray for easy installation
- Press fit terminals loop in loop out
- · Rear and end conduit entry points
- Emergency and microwave dimmable and on/off and PIR options















General Information

Mounting

Trade Name

Environment

Product Group

Color Finish

Product Shape

Product Range

Overall Dimensions

Length (mm)

Width (mm)

Height (mm)

Light Source

Light Source Features

Recommended product location

IP Rating

Origin of manufacturer

Warranty
Driver manufacturer

Surface Mounted

Skypack™ QR

Indoor

LED - Surface

White

Rectangular

Skypack™

1638 x 70 x 76.5

1368

70

76.5

LED

Neutral White

Domestic, Commercial and Industrial Applications

IP20

Made In China

5 Year Warranty (See Website for terms and conditions)

JCC

LED manufacturer/type XINDA

Lighting Product Type 1 Linear Lighting

Customs Tariff code** 9405119090

Electrical

Voltage Rating 220-240

Primary Running Current(Amp) 0.16-2.1

Operating Frequency Hz 50/60Hz

Secondary running current(mA) 900

Constant Current or Constant Voltage CC

Luminaire Circuit Wattage 37

Class

EMC Compliant (EN55015)

Yes

Power Factor Correction

0.9

Input Electrical Connections Live, Earth & Neutral

Dimmable No.

Thermals

Operating Temperature Range °C 0-45

Performance Data

LED Life (Hours)* 54000

Energy Rating

This product contains a light source of energy efficiency

class E

Actual Lumen Output 4440

Lumens Per Circuit Watt 120

Color Rendering Index 80-89

CRI: Ra 80

Correlated Color Temperature 4000K

Beam Angle ° 120

LOR (Light Output Ratio) % 100

Photometry Available Yes

Controls and Sensors

Detection Distance 10m max

Detection Motion Speed 0.6-15m/s

Installation Height 2-6m

Detection angle 360° (ceiling mount)

Hold time 10sec/30sec/90sec/5min/10min/30min

Lux settings 3lux/30lux/300lux/2000lux

Transmitting power 0.5W+/-5%

Construction

Primary Material Steel

Packaging

Product Packaged Weight(kg)

Product Bar Code EAN-13 Number

1.176

5052544118432

Standards & Approvals

Manufactured in accordance to

CE Marked

UKCA Marked

Date code/Purchase order No.

WEEE symbol

Certificate Of Conformity

Accredited Members

BS EN 60598:2015, 2-1,2-22

Yes


Yes


Yes

Yes

Available on request

LIA, ISO9001-2015, ISO14001-2015







*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

**JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT. Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk Company Registration Number: 03044848 | VAT Number: 918544112